



PATENT ABSTRACTS OF JAPAN

(11) Publication number: **58193379 A**(43) Date of publication of application: **11.11.83**

(51) Int. Cl.

C25B 9/00**C25B 1/46****C25B 13/00**(21) Application number: **57073323**(22) Date of filing: **04.05.82**(71) Applicant: **ASAHI GLASS CO LTD**(72) Inventor: **SHIBATA HIDENORI
ICHIMURA TAKASHI****(54) ELECTROLYTIC CELL FOR ALKALI CHLORIDE****(57) Abstract:**

PURPOSE: To inhibit the deformation of an ion-exchange membrane, in performing electrolysis while forming the difference in pressure between electrode chambers, by providing a member for inhibiting the deformation of the ion-exchange membrane inside the chambers.

CONSTITUTION: When operation is performed in a vertical electrolytic cell for an alkali chloride having an ion-exchange membrane as a diaphragm while forming

the difference in pressure between cathodic and anodic chambers, a member for inhibiting the deformation of the ion-exchange membrane is provided inside the electrode chambers in a manner such that the ion-exchange membrane is not pushed from the side of the high-pressure electrode chamber to the low-pressure electrode chamber. Side member for inhibiting the deformation is pref. a heat and corrosion-resistant material, e.g. polypropylene, polyethylene or polytetrafluoroethylene.

COPYRIGHT: (C)1983,JPO&Japio